



projectiondesign evo+

The evo+ has been designed specifically for business users and offers the best possible performance for the meeting room or the distinctive boardroom. DLP™ (Digital Light Processing) technology yields superb performance with high brightness, true colours and excellent contrast. Combined with its small size and extremely low operating noise the evo+ is the ultimate meeting room projector, with qualities unheard of in its class.

designed for ease of use

Sharp attention to detail coupled with a focus on ease of use has resulted in a very distinct projector that is as attractive in design as it is in performance. Evolved from an internationally recognized and award winning design, the evo+ is finished in an eye catching Ice Blue magnesium cabinet. This ensures the best possible durability and longevity as well as lowering the total cost of ownership. Using the evo+ is simply a question of switching it on and connecting. Everything else is automatic. It couldn't be easier.

investment for the future

The extensive connectivity of the projectiondesign evo+ allows it to connect to everything in the office, and ensures it will be a long lasting investment that will never go out of style. The evo+ will be an integral part of the office environment for many years, and will never fail to perform in front of your audience

The choice of a lifetime. projectiondesign evo+.

 **Award for Design Excellence**
Awarded by the
Norwegian Design Council

 **Designed and
manufactured
in Norway**





diagonal image size	distance	
	cm / inches	min
152 / 60	268	340
203 / 80	358	455
254 / 100	447	569
304 / 120	536	683

technical specifications

projector	evo+ XGA DLPTM digital projector (101-0071-06)
resolution	1024 x 768
brightness	2600 ANSI lumens
contrast ratio	2000 : 1 (on / off)
computer video	pc / mac, 640 x 480 - 1400 x 1050 1080i, 720p, pal, ntsc, secam
projection lens	1.3x manual zoom lens
throw ratio	2.20 - 2.80 : 1 distance : width
image size	0.7 - 5.7 m (2.5 - 18 ft) diagonal
lens offset	+13 % of image height
focusing distance	1.5 - 10 m (5 - 33 ft)
lamp	250 w uhp TM , 4000/2000 hours (ecomode/fullpower)
computer inputs	2x 15 pin HDDSUB (analog RGB) 1x DVI-D (digital RGB)
video inputs	3x RCA (component YUV) 1x 4-pin Mini DIN (S-video Y/C) 1x RCA composite video
video out	1x VGA (analog rgb)
control and communication	2x RS232 9-pin DSUB (control) in/out 1x RJ45 TCP/IP network port 1x USB (mouse control and firmware upgrade) 1x 3.5mm mini jack RC repeater
audio line out	2x 3.5 mm stereo mini jack (data-video)
speakers	2x 1 w stereo
supplied cables	vga cable dvi-d cable usb cable a/v cable
supplied accessories	ceiling mount cable cover infrared remote control soft carrying case
operating noise level	28 dB (typical)
dimensions	244 x 278 x 88 mm (9.6 x 10.9 x 3.5 in) dwh
weight	3.0 kg / 6.5 lbs
power requirements	100 - 240 vac, 50/60 Hz, +/- 10 %
conformances	350 w power consumption
warranty	CE, CSA "C/US", FCC Class A 2 years, 90 days or 500 hours on lamp



All brands and trade names are the property of their respective owners.
Specifications subject to change without prior notice. All values are typical and may vary.
Patent pending on lamp and cooling system.